



Simple and versatile design. Can be 'hand-held' or 'threaded' using a compression fitting. Suitable for numerous applications. Available in various sensor types.

## STANDARD SPECIFICATIONS:

316SS IMMERSIBLE INSERTION STEM GROUNDED (THERMOCOUPLE) 3-WIRE 385 1/3DIN (RTD Pt100)





OPTIONS	CODE
INSERTION STEM MATERIAL: ICONEL 600 (HIGH TEMPERATURE)	600
INSERTION STEM MATERIAL: 446SS (CORROSION RESISTANT)	446
FLEXIBLE SS ARMOUR OVER LEAD CABLE	A
LEAD CABLE WITH SS OVERBRAID	SS
EXPOSED SENSOR TIP (AIR SENSOR)	E
SHARP CHISEL TIP (PENERATION)	S
SUBMERSIBLE	SUB
TEFLON-COATED INSERTION STEM	TF
TRANSITION FITTING W/STRAIN RELIEF	R
4-WIRE RTD	4W
DUAL SENSORS	D
UNGROUNDED THERMOCOUPLE JUNCTION	U
COMPRESSION FITTING (CS - STAINLESS STEEL) (CB - BRASS)	
- 1/2"NPT	CS2 or CB
- 1/4"NPT	CS4 or CB
- 1/8"NPT	CS8 or CB
OTHER OPTIONS (SEE M02 OPTIONS)	0()



1295 Morningside Avenue, Unit 16-17 Toronto, ON MIB 4Z4 Canada Phone: 416-261-4865 Fax: 416-261-7879 www.scigiene.com

